

### Technical Data

Rated Voltage:415V

Current Rating:63A

Busbar Cross Section:16mm<sup>2</sup>Cu

Standard Length:1 m

### Catalog NO.





Diagram	Type Designation	Code
<b>For single pole device</b> 	Pin Busbar 32A SP	1410321
	Pin Busbar 63A SP	1410631
	Pin Busbar 80A SP	1410801
	Pin Busbar 100A SP	1411001
	Fork Busbar 32A SP	1420321
	Fork Busbar 63A SP	1420631
	Fork Busbar 80A SP	1420801
	Fork Busbar 100A SP	1421001



<b>For 2-pole device</b> 	Pin Busbar 32A DP	1410322
	Pin Busbar 63A DP	1410632
	Pin Busbar 80A DP	1410802
	Pin Busbar 100A DP	1411002
	Fork Busbar 32A DP	1420322
	Fork Busbar 63A DP	1420632
	Fork Busbar 80A DP	1420802
	Fork Busbar 100A DP	1421002



<b>For 3-pole device</b> 	Pin Busbar 32A TP	1410323
	Pin Busbar 63A TP	1410633
	Pin Busbar 80A TP	1410803
	Pin Busbar 100A TP	1411003
	Fork Busbar 32A TP	1420323
	Fork Busbar 63A TP	1420633
	Fork Busbar 80A TP	1420803
	Fork Busbar 100A TP	1421003



<b>For 4-pole device</b> 	Pin Busbar 32A FP	1410324
	Pin Busbar 63A FP	1410634
	Pin Busbar 80A FP	1410804
	Pin Busbar 100A FP	1411004
	Fork Busbar 32A FP	1420324
	Fork Busbar 63A FP	1420634
	Fork Busbar 80A FP	1420804
	Fork Busbar 100A FP	1421004



<b>For 1P+N device (MCB AUB1N)</b> 	Pin Busbar 32A 1P+N	1410325
--	---------------------	---------